



Textastic for iPhone Manual

Textastic for iPhone Manual

1 Viewing and Editing Files

1.1	How does the additional row of keys above the standard keyboard work?	4
1.2	How can I move the cursor using swipe gestures?	7
1.3	Which keyboard shortcuts can I use with an external hardware keyboard?	10
1.4	Which file types are supported?	11
1.5	How can I add my own syntax definitions, themes and templates?	14
1.6	Which URL schemes can be used to call Textastic from other apps?	22
1.7	How can I show a list of recently opened files?	23
1.8	How can I view an image file or open it in another app?	27
1.9	When does Textastic save file changes?	30

2 Importing and Managing Files

2.1	How do I open files from other apps?	32
2.2	How do I import files using a USB connection?	36
2.3	How can I move, copy and rename files and folders?	39

3 Connecting to Remote Servers

3.1	How do I connect to an FTP, FTPS or SFTP server?	47
3.2	How can I quickly upload downloaded files?	59
3.3	How do I access files in my Dropbox account?	64

4 Connecting via Wi-Fi / built-in WebDAV server


4.1	Why do I need WebDAV and which clients are supported?	72
4.2	Starting the WebDAV-Server	73
4.3	Connecting to Textastic with Finder	79
4.4	Connecting to Textastic with Windows Explorer	84

Viewing and Editing Files

How does the additional row of keys above the standard keyboard work?

Textastic adds a set of additional keys above the standard keyboard. These allow you to enter 40 different special characters quickly without having to switch to another keyboard layout or scrolling a list of keys and also add direct access to undo and redo.


Using the swipeable keys



If you want to enter the character in the middle of the button, just tap on the button.

If you want to enter one of the other four characters, make sure to **swipe over the button in the direction of the character** you want to type.

Tab key



The first swipeable key in the row has some special functions:

Tap on the key to enter a **tab character**. If text is selected, pressing the tab key will **indent the selected lines**. This is equivalent to "Shift Right" in the editing menu.

The character in the top left corner is an **"untab" character**. It has the reverse effect of the tab character and allows you to **unindent selected lines**. This is equivalent to "Shift Left" in the editing menu.

The character in the top right corner is **forward delete**. It deletes the character that follows after the cursor and is the equivalent of the "Del" key on regular keyboards.

The bottom left character moves the cursor to the **beginning of the current line**.


The bottom right character moves the cursor to the **end of the current line**.

Undo and redo



Tap on the arrow pointing to the right to undo your last editing step. Tap on the right arrow for redo.


Dismissing the keyboard



Tap on the button in the top right corner to dismiss the keyboard.

How can I move the cursor using swipe gestures?

You can use swipe gestures to quickly move the cursor when you are editing text.



The following gestures only work when the keyboard is up:

Swipe in the direction you want to move the cursor (left or right).

Swipe with **one finger** to move **one character** at a time.

Swipe with **two fingers** to move **to the next word boundary**.

Swipe with **three fingers** to move **to the start or end of the current line**.

Which keyboard shortcuts can I use with an external hardware keyboard?

Here you can find a list of keyboard shortcuts you can use when you connect a wireless bluetooth keyboard or a keyboard dock to your iPad. These shortcuts work in all iOS apps.

Keyboard Shortcuts

Keyboard shortcuts supported by iOS / iPad:

- **Cmd+A** - Select All
- **Cmd+C** - Copy
- **Cmd+X** - Cut
- **Cmd+V** - Paste
- **Cmd+Z** - Undo
- **Cmd+Shift+Z** - Redo
- **Shift+Arrow** - Select text
- **Cmd+Up/Down** - Move cursor to the beginning/end of the file
- **Cmd+Left/Right** - Move cursor to beginning/end of the current line
- **Alt+Left/Right** - Move cursor to the previous/next word
- **Esc** - Bring up virtual on-screen keyboard
- **Alt-Delete** - Delete the word to the left of the cursor
- **Cmd-Delete** - Delete everything on the current line to the left of the cursor

iOS also supports these **Emacs** keybindings:

- **Ctrl-A** - Move cursor to the beginning of the line
- **Ctrl-E** - Move cursor to the end of the line
- **Ctrl-F** - Move cursor forward one character
- **Ctrl-B** - Move cursor backward one character
- **Ctrl-K** - Kill/delete text between cursor and the end of the line
- **Ctrl-H** - Delete one character to the left

Textastic also supports these special shortcuts:

- **Tab** - Indent selected text
- **Shift-Tab** - Unindent selected text

Note: Unfortunately, the standard shortcuts are entirely provided by the iOS operating system and there's no way for third party developers to extend them with custom shortcuts that use modifier keys like Ctrl, Cmd or Alt.

Which file types are supported?

A list of supported programming and markup languages.

Supported file types

Textastic has **syntax highlighting support** for the following plain text file types:

- ActionScript
- Active4D
- Ada
- Apache (conf, htaccess)
- AppleScript
- ASP, ASP vb.NET
- BibTeX
- C
- C#
- C++
- CoffeeScript
- ColdFusion
- CSS
- CSV
- D
- Diff
- DokuWiki
- Dylan
- Eiffel
- Erlang
- Fortran
- Grails Server Page
- Groovy
- Haskell
- HTML (various variants)
- Ini
- Java
- Java properties
- Java Server Page
- JavaScript
- JSON
- LaTeX
- LESS
- LilyPond
- Lisp


- LiveCode
- Logo
- Linden Scripting Language (LSL)
- Lua
- Mail
- Makefile
- Markdown
- MATLAB
- Mediawiki
- MEL
- MIPS Assembler
- Modula-3
- MulitMarkdown
- Nemerle
- Objective-C
- Objective-C++
- OCaml
- Octave
- Pascal
- Perl
- PHP
- PowerShell
- Prolog
- Property List
- Python
- R
- Regular Expressions
- RJS
- Ruby
- Ruby Haml
- Ruby on Rails
- Scala
- Scheme
- Shell Script
- SQL
- SSH Config
- Stata
- Strings File
- TCL
- TeX
- Textile
- TSV
- Verilog

- VHDL
- XML
- XSL
- YAML


Note: Textastic uses syntax definitions and themes from [TextMate](#). You can also [add your own syntax definitions and themes](#).

How can I add my own syntax definitions, themes and templates?


Textastic allows you to add your own custom syntax definitions and themes. You can add [TextMate](#)-compatible **.tmbundle** packages and **.tmTheme** files. You can also add custom file templates that appear in the file creation screen.




Go to the root folder in the *Files* section. Tap on the "+" button.



Choose "Folder" and enter "#Textastic" in the *Folder Name* field. Tap "Done".




Make sure the newly created folder has a **special icon** as seen in the screenshot. The name of the folder is case sensitive.



Copy your .tmbundle TextMate bundles and .tmTheme themes into the newly created directory.

You can use Dropbox, FTP or the WebDAV server to do that.


Restart the app



The new files are loaded on application startup. Please restart the app for changes to take effect.

To do this, leave the app by tapping on the home button once. Then open the task switcher by hitting the home button twice, and then hold down on Textastic until the icon starts jiggling. A red “-” should appear on the corner of the app icon. Press it to quit the app.

After you start the app, the new syntax definitions can be chosen in the *File Properties* popover. You can select added themes in the settings screen.



You can also add your own templates that you can select in the file creation dialog.

You can find a detailed description and example files at

<https://github.com/blach/Textastic-Customization>

Which URL schemes can be used to call Textastic from other apps?

Textastic exposes actions that can be used by other apps using the x-callback-url specification. The *textastic://* scheme can also be used to view the source code of websites.


Supported URL schemes

You can find detailed information about the supported URL schemes [in this document](#).


The *x-callback-url* API is supported by Textastic 4.4 and later.

How can I show a list of recently opened files?

Using the *Recent Files* list you can quickly switch between different files - even when they are located in different folders. This popover also has a button to close the currently open file.



You can show a list of *Recent Files* by **tapping on the name of the current file** above the editor.




Switch to a file by choosing it from the list.

Use the **Clear List** button to remove all files from the list or tap on the **Edit** button to delete only

some of the files from the list.

How can I view an image file or open it in another app?

Textastic supports the preview function of iOS which allows you to view image, pdf and office files.



Tap an image, pdf or office file to show a preview.

Tap and hold a file and tap on "**Open In...**" to open the file in another app that can edit or view this

type of file.

When does Textastic save file changes?

Here you can find details about the saving mechanism.

Notes


Textastic **automatically saves file changes every 10 seconds** and when the file is closed to open another file.

By using the **Undo** button you can undo changes in the currently open file.

Importing and Managing Files

How do I open files from other apps?

Many iPhone apps support the **Open In...** menu. See some examples.




If you have an email with plain text attachments, simply tap and hold it.

Use the **Open In "Textastic"** command if available, or the **Open In...** menu to open this attachment

in Textastic.

Good Reader



- 1) Tap on the **Actions** button
- 2) Select the file you want to open with Textastic.
- 3) Tap on the **Open In...** button

4) Choose **Textastic**

How do I import files using a USB connection?

Learn how to use iTunes File Sharing to copy files between your computer and Textastic using a USB connection.


Requirements

- iTunes 9.1 or later
- Mac OS X v10.5.8 or later, or Windows XP SP3 or later

Connect iPad

Connect iPad to your computer using the included **Dock Connector to USB cable**.

Launch iTunes




Launch iTunes 9.1 or later on your computer.

Select device



Select your iPad from the Devices section of iTunes.


Go to File Sharing



Click the **Apps** tab and scroll down to the bottom of the page.


Note: If you do not see the File Sharing section shown in the image above, your iPad does not have any apps that support File Sharing. Install Textastic first.

Choose Textastic



Under the File Sharing section, you'll find a list of apps currently installed on your iPad that support File Sharing. Select Textastic to view a list of the files associated with that app on your iPad.

Copy files between your computer and Textastic



Drag and drop files onto the Documents list to copy them to the app on your iPad

or...


Click the **Add...** button, locate the file or files you want to copy from your computer, and click the Choose button. The selected files will be copied to the app on your iPad immediately.

or...


Select the file or files you want to copy to your computer from the Documents list and click the **Save to...** button. Locate the folder on your computer to which you want to copy the files and click the Choose button. The selected files will be copied to your computer immediately.

How can I move, copy and rename files and folders?

Learn how to use edit mode in the Files section. This allows you to move, copy and rename local files and folders.



Tap on the **Edit** button in the Files section to enable the edit mode.




You can select files and folders by tapping on them.


Using the buttons on the bottom you can **Delete** (1), **Move** (2) and **Zip** (3) the selected files and

folders. Those buttons become active as soon as at least one file is selected.

Tapping on the **button** (4) on the right side of each item, you can **Rename** and **Copy** the file or folder.



If you tapped on the **Move** button in the previous screen, Textastic will bring up a list of your folders. Choose the folder where you want to move the selected files or folders.



If you tapped on the button on the right side of a file or folder, you can choose to **Rename** or **Copy** it.

Enter new name

Carrier 16:57

Cancel Copy Folder Done

New Folder Name

Copy of js


Q W E R T Y U I O P
A S D F G H J K L
↑ Z X C V B N M ↵
123 globe space return

If you choose to copy or rename a file or folder, Textastic will ask for a new name.

Connecting to Remote Servers

How do I connect to an FTP, FTPS or SFTP server?

Learn how to configure a new FTP, FTPS (FTP over SSL), FTPES (FTP over Explicit Auth SSL) or SFTP (SSH File Transfer Protocol) connection.



Tap on the **File Transfer button** in the **Files** section to open the File Transfer screen.



Tap on the **+** button (1) and choose **(S)FTP Connection** (2) to add a new connection.

Carrier 16:59

Local Remote Done

Cancel (S)FTP Connection Done

Title Optional

Protocol FTP (Unencrypted) >

Host textasticapp.com

Port 21

User user

Password ●●●●●●●●●●

Path Example: /httpdocs/

Encoding Unicode (UTF-8) >

Choose the "FTP (Unencrypted)" **protocol**.

Configure the connection by setting the **host name** (this can be a domain name like

"example.com" or an ip address), a **user name** and a **password**.

You can also add a custom **title** that will appear in the connection list and choose another port than the standard port 21.

If you enter a **path**, Textastic will use this as the root path when connecting to the server.

Choose the correct character **encoding** you want to use for this connection. This setting depends on your server's configuration.

If you encounter connection problems with the standard "Passive (PASV)" **connection mode**, try to use "Active (PORT)" instead.

Enable the **Show Hidden Files** setting if you want to see hidden remote files like **".htaccess"**.

You can also try to enable the **Debug Log** setting. This will create detailed log files in the "logs" directory in Textastic. Note that **this logs all traffic for this connection**, so only enable this for debugging purposes and make sure to disable it again as soon as possible.

Carrier 17:00

Local Remote Done

Cancel (S)FTP Connection Done

Title Optional

Protocol FTPS (FTP over... >

Host textasticapp.com

Port 990

User user

Password ●●●●●●●●●●

Path Example: /httpdocs/

Encoding Unicode (UTF-8) >

For FTPS / FTP over SSL connections, most settings are the same as for regular FTP connections (see above). Notice the **different default port 990**.

You can also choose FTPES (FTP over Explicit Auth SSL) as protocol which defaults to port 21.

FTPS adds an option that allows you to choose if Textastic **verifies the SSL certificate** of the server. Disable this if you use a **self-signed certificate** on the server.

Carrier 17:00

Local Remote Done

Cancel (S)FTP Connection Done

SFTP

Public Key Auth. ON

Private Key File /ssh/id_rsa

Please enter the local path to the private key file. You can transfer the key file to Textastic using iTunes File Sharing or Dropbox. The file format of ssh-keygen is expected (accepts RSA and DSA keys).

If necessary, the password specified above is used as the passphrase for the private key file.

SFTP (SSH File Transfer Protocol) is a subsystem of SSH (Secure Shell). You can use this connection type to securely transfer files between your server and Textastic. For more information have a look at [SSH File Transfer Protocol \(Wikipedia\)](#)

The **default port** for SFTP connections is **22**.

Textastic usually switches to the root directory after establishing an SFTP connection. If you want to start at the **user's home directory** instead, enter "~/" in the **Path** field.

Textastic supports user/password authentication as well as public key authentication.

1. User/Password authentication

Enter your user name and password as you would for a regular FTP connection, but disable the **Public Key Auth.** setting.

2. Public Key Authentication

Enter the **user name**.

Enable the **Public Key Auth.** setting. Now you can enter the path to the private key file.

For this to work, you need to transfer the private key file for your SSH account to Textastic. You can do this by using [iTunes File Sharing](#) (via USB), [Dropbox](#) or the built-in [WebDAV](#) server (via Wi-Fi).

The standard settings expect a private key file named "id_rsa" in the local "ssh" subfolder in Textastic. If you used iTunes File Sharing, the file will be in the root folder, so you can either enter "id_rsa" as the private key file path or [move the file to a subfolder](#).


If your private key file is protected with a **passphrase**, Textastic uses the **password** setting to retrieve the private key.

Textastic expects the key file to be in the format used by the **OpenSSH utility "ssh-keygen"**. If you instead have a key in PuTTY's format (.ppk), you can use PuTTYgen to convert it to OpenSSH format:


Visit the [PuTTY website](#) and download *puttygen.exe* (on your PC). Open it, and using the *File* menu, load your .ppk that you already use, and type in your passphrase. Now go to the *Conversions* menu and export the key as an OpenSSH key. You can now use the converted key with Textastic.

If you encounter connection problems, you can enable the **Debug Log** setting. This will create detailed log files in the "logs" directory in Textastic. Note that **this logs all traffic for this connection**, so only enable this for debugging purposes and make sure to disable it again as soon as possible.

Save Connection



Tap **Done** to save this connection.



You can now tap on the newly created connection to connect to the remote server.



textasticapp.com



You can change the settings of a connection by tapping on the blue arrow on the right side of a connection.

How can I quickly upload downloaded files?


Textastic offers a fast and easy way to upload files you downloaded from a remote server. You can also download the latest version if you know that the file was changed on the remote server.

Open File Properties

```
eb, ide, ftp, sftp, dropbox, textmate  
" />  
<meta name="description"  
content="Textastic is a text  
editor for iPad with rich  
support for syntax highlighting,
```




Tap on the file properties button below the editor.



When you upload or download files from a remote server (Dropbox, FTP or WebDAV), Textastic saves the connection used for the download as well as the remote path of the file. You can see this information in the **File Properties** popover.

You can save several remote locations per file by uploading the file to another location or downloading the file from another location and overwriting the local file in the File Transfer screen (tap on the "globe" button).

You can tap on the **path** to see the full remote path.



When a file is linked to a remote connection, there are two new options when you tap on the **Action** button:

Upload This File: This uploads the currently open file to the same remote location it was originally downloaded from


Download Latest: This will connect to the remote server and try to download the latest version of the file

If there are links to more than one remote connection, Textastic will ask you which one to use.

This lets you quickly upload your changes or update your downloaded files.

How do I access files in my Dropbox account?


Learn how to access your Dropbox account.



Tap on the **File Transfer button** in the **Files** section to open the File Transfer screen.



Tap on the **+** button (1) and choose **Dropbox Connection** (2) to add a new Dropbox connection.



You can add a custom **title** that will appear in the connection list (especially useful if you want to connect to several different Dropbox accounts).


Tap on **Not Linked**.

Enter Dropbox credentials

Carrier 17:07

Local Remote Done

Cancel Link Account 3 Link

 **Dropbox**


Linking will allow this app to access
and modify files in your Dropbox

Email alexander@example.c... 1


Password ●●●● 2

New to Dropbox? **Create an account**

Enter the **Email** (1) and **Password** (2) for your Dropbox account and tap on the **Link button** (3) to link your Dropbox account to this connection.



The Dropbox Connection is now linked to your Dropbox account. Tap on the **Done** button.



You can now tap on the newly created connection to connect to your Dropbox account.

Connecting via Wi-Fi / built-in WebDAV server

Why do I need WebDAV and which clients are supported?

The built-in WebDAV server allows you to easily transfer files to Textastic from your Mac or PC via Wi-Fi.

Supported Clients

Windows and Mac OS X include WebDAV clients so you can use Windows Explorer and Finder to manage the files in Textastic.

Textastic is tested against Mac OS X **Finder**, Windows **Explorer** (Vista and Windows 7), [Cyberduck](#), [BitKinex](#) and the [Total Commander](#) WebDAV plugin.


More

If you want to know more about WebDAV, consult the excellent [Wikipedia article on WebDAV](#).

Textastic 2.2 also includes a WebDAV client in addition to the WebDAV server.

Starting the WebDAV-Server

Learn how to configure and start the builtin WebDAV server in order to manager your files via Wi-Fi.



Tap on the **Wi-Fi button** to open the WebDAV screen.

WebDAV Server Done

Settings

User textastic ¹

Password ●●●●●●●●

Port 80 ²


Server Started ☐ OFF

Connection Info

WebDAV URL http://10.0.1.5:80/

The WebDAV server always asks for user credentials. **By default, the user name is "textastic" and the password is "password"**. It's recommended to change these settings before starting the server. (1)

You can choose a custom port or use the default port 80 (2).



Start the WebDAV server by flipping the "**Server Started**" switch to **ON**.

Use a WebDAV client to connect to Textastic

Connect to the server you just started [from your Mac](#) or [from Windows](#).

Notes


Textastic will not enter standby mode as long as the WebDAV server is running. Use the power button on your iPhone to manually put it to sleep.

For security reasons, the WebDAV server is **not automatically restarted** when you close and then re-open the app. This is to prevent the app from exposing your files without your knowledge.

Connecting to Textastic with Finder

Learn how to connect to the builtin WebDAV server using Finder on Mac OS X.

Requirements



Your Mac must be connected to the **same network** as your iPhone running Textastic.


The iPad must be **connected via Wi-Fi**.

Make sure the WebDAV server is started



[Start the WebDAV server](#) and note the WebDAV url.


Open "Connect to Server" dialog



Switch to Finder.

Open the **Go** menu (1) and select **Connect to Server** (2).

Connect



Enter the url from the Textastic WebDAV screen (1) and click on **Connect** (2).


Enter credentials



Enter user name and password you chose when setting up the WebDAV server. (Defaults are "textastic" and "password"). (1)

Click on **Connect** (2).

Manage your files




You can now use Finder to manager your files.

Connecting to Textastic with Windows Explorer

Learn how to connect to the builtin WebDAV server using Explorer on Windows.

Requirements



Your Windows PC must be connected to the **same network** as your iPad running Textastic.


Textastic currently supports Windows Vista and Windows 7. If you need to connect from older

versions of Windows (like XP), please use a third party client like [BitKindex](#) or [Total Commander](#) with [WebDAV-Plugin](#).

The iPad must be **connected via Wi-Fi**.

It is recommended that all Vista users install [this WebDAV/Web Folders update from Microsoft](#).
(This is not required on Windows 7)

Make sure the WebDAV server is started



[Start the WebDAV server](#) and note the WebDAV url.

Windows Vista/Windows 7 users have two options for connecting to the Textastic WebDAV server: You can either map a network drive to the Files server, or create a network location. Both methods are described below.

1) Map a Network Drive

1. Open **Computer** from the Start Menu.
2. Click on the **Map Network Drive** button in the toolbar.
3. Enter the Textastic **WebDAV URL** into the Folder field.
4. Click the blue link "**Connect using a different username**" to enter your username and password.
5. Click **Finish** to create the new drive letter.

This will map Files to a network drive with a name such as: "DAVWWWRoot (\192.168.63.176@80) Y:"

To reconnect in future just open this network drive from Computer.

Note: If you change your username or password you may need to re-create the Network drive to gain access to Files.

2) Create a Network Location

1. Open **Computer** from the Start Menu.
2. Click on the **Map Network Drive** toolbar item.
3. In the Map Network Drive window, click **Connect to a Web site that you can use to store your documents and pictures**, click Next.
4. Select **Choose a custom network location**, click Next.
5. In the Internet or network address field, enter the Textastic **WebDAV URL**
6. You will be prompted for your **username and password**.
7. Enter a **name** for the connection and click **Next**.
8. Ensure that **Open this network location when I click Finish** is checked and click Finish.

In the future you can connect simply by opening "My Network Places" and double-clicking the network location you created. You may need to select "Refresh" from the window's context-menu to ensure that Windows has an up-to-date view of your files and folders.

Note: If you change your username or password you may need to re-create the Network location to gain access to Files.